

OPERATION/USE

Inflate & Go high jump landing system is intended to be used with adult supervision.

1. Check pit landing area for any sharp objects
2. If using on rough surface lay down appropriate sized tarp or protection sheet (not supplied). (fig. 1)
3. Remove inflatable bladder from storage container (by pulling on 1" straps under bladder) and lay on landing area or protective tarp. (see fig. 2)
4. Hook-up tubing to blower. (fig 3)
5. Plug in unit to 110v grounded outlet and turn unit on. (fig 4)
6. Secure pit in place using loops on bottom of pit (secure to anchors or sandbags, DO NOT USE TOPCOVER CLIPS TO ANCHOR TO GROUND) (fig 5)
7. Unit will fully inflate within 2-3 minutes. (fig 6)
8. Unfold foam top cover on base unit and attach to base. (fig 6 & 7)
9. Check pit for complete inflation before attempting to jump on pit.

STORAGE

1. Switch tubing from blower opening to suction opening. (fig 8)
2. Make sure lid of storage container is closed. (blower will not remove air without the lid closed)
3. As pit deflates, remove foam cover, roll up and fold in half. (fig. 9 & 10)
4. When pit is fully deflated, fold inflatable bladder in thirds and fold, starting with the opposite end of tubing with first fold being approximately 12-18" wide. (fig. 11 & 12)
5. Shut blower off.
6. Place bladder in storage container and close lid. (fig 13 & 14)
7. Lay folded foam top cover on storage container. (fig 15)
8. Store unit indoors in a clean dry environment to ensure long life.