



A.S.K. Enterprise, Inc.
812 56th Street
West Des Moines,
IA 50266
Phone: 515.229.6734

Vinyl Repair Instructions

1. Remove all loose ends or rough edges from tear and if possible make sure torn surface is flat.
2. Remove all dirt, grease and moisture from surfaces.
3. Clean surface with alcohol wipes and let surface dry thoroughly.
4. Cut patch 1” – 2” larger in width and length than the rip or tear. (avoid square corners on patch)
5. Apply thin coat of HH-66 Vinyl Cement to **patch** and **cleaned pit surface**(let dry 30-45 seconds or until glue is cloudy)
6. Apply patch to torn surface avoiding wrinkles or bubbles in surfaces.
7. Let set for 10 minutes before use.

Precautions

**Danger – Flammable Mixture.
Do Not Use Near Fire or Flame.
Use with Adequate Ventilation.
Vapor May Cause Flash Fire.**

**Avoid Prolonged Breathing of
Vapor and Contact With Eyes and
Skin.**



A.S.K. Enterprise, Inc.
812 56th Street
West Des Moines,
IA 50266
Phone: 515.229.6734

info@inflateandgo.com

www.inflateandgo.com

Products: Inflatable High Jump Pits * High Jump Standards * Storage Units Flexible Practice Bar